



C O N C R E T E N A T I O N

CARE & MAINTENANCE GUIDE

We are sure that you will enjoy your new basin for years to come. When properly sealed they are very easy to maintain.

- Clean your basin using a mild non-abrasive cleanser. Please refrain from using scour pads on the concrete, as it can scratch your basin and breakdown the sealer.
- Avoid exposure to products with high levels of PH such as paint strippers, bleach, and nail polish remover. If exposure occurs, rinse immediately with water to neutralize effect, and then follow usual cleansing procedure.

Stubborn Stains and Dried Spills

For dried spills, a wet cloth is recommended. For stubborn stains, use a non-acidic and non-abrasive cleanser such as Cerapol. Avoid forceful scrubbing as this may result in loss of shine and remove the protective sealer.

Direct Sunlight

Direct sunlight can cause concrete to slowly discolour over a long period of time.

Localised Heat

Concrete expands when it is exposed to heat. Avoid excessive exposure to localized heat, as this may result in damage to your basin.

Scratches, Cracks, and Edge Chipping

Overtime, your basin may develop scratches and marks from day to day use. Try to avoid impact on edges and the surface with hard objects. If damage should occur, the surface can be refinished by sanding and re-sealing the basin. Contact Concrete Nation if you would like more information on refinishing.

*****PLUMBERS PLEASE NOTE*****

Installation of waste must include rubber seals on the top and bottom of the basin. If these are not included it will void the warranty of the basin.

Distributed by:

Plumblīne

T 04 568 9898 E sales@plumblīne.co.nz
www.plumblīne.co.nz